



NOTES:

1. CLEANOUT COVER TO BE FLUSH WITH THE FINAL GRADE. RESTORE SURFACE TO MATCH EXISTING CONDITIONS IN ACCORDANCE WITH CMUD STANDARD SPECIFICATIONS AND DETAILS.
2. LOCATION OF CLEANOUT SHALL BE AS DIRECTED BY ENGINEER.
3. NEW SERVICE LATERAL PIPE, CLEANOUT PIPING AND FITTINGS SHALL BE DUCTILE IRON PIPE (DIP) OR PVC. NEW SERVICE LATERALS SHALL BE INSTALLED TO MATCH THE EXISTING SLOPES AND CONFIGURATIONS UNLESS NOTED OTHERWISE. REFER TO DETAIL F.
4. CLEANOUT CAP SHALL BE PLASTIC GRIPPER PLUG, END OF PIPE MODEL, BY CHERNE INDUSTRIES OR APPROVED EQUAL.
5. FOR MEASUREMENT AND PAYMENT, CLEANOUT TO BEGIN AT WYE FITTING.

CHARLOTTE-MECKLENBURG UTILITIES
CHARLOTTE, NORTH CAROLINA

TYPICAL CLEANOUT

No.	Date	By	Revision	NTS Scale	Approved By	DETAIL NO. G
-----	------	----	----------	--------------	-------------	-----------------