



KEY/ANCHOR MATERIAL AT TOP OF SLOPE.

12" MIN. SPACING TYP.*

36" MIN. SPACING TYP.*

6" OVERLAP IN SLICE

WATER TABLE

NON-WOVEN GEOTEXTILE FILTER CLOTH FABRIC 4' ABOVE SOURCE WATER.

KEY/ANCHOR MATERIAL TO TOE OF SLOPE.

GENERAL NOTES:

1. LAY BLANKETS LOOSELY AND STAKE OR STAPLE TO MAINTAIN DIRECT CONTACT WITH THE SOIL. DO NOT STRETCH.
2. * DIMENSIONS SHOWN ARE MINIMUM, MANUFACTURED PRODUCTS MAY HAVE ADDITIONAL REQUIREMENTS THAT MUST BE MET.
3. SLOPE SURFACE SHALL BE FREE OF ROCKS, SOIL CLODS, STICKS, GRASS. MAT/BLANKETS SHALL HAVE GOOD SOIL CONTACT.
4. THE DETAIL SHOWN IS FOR SLOPE MATTING. FOR CHANNEL OR PIPE OUTFALL MATTING SPECIFICATIONS, PLEASE REFER TO NCESCPDM STANDARD #6.17 AND MANUFACTURER'S GUIDELINES.

NOT TO SCALE



**CITY OF CHARLOTTE
LAND DEVELOPMENT STANDARDS**
INCLUDES CHARLOTTE ETJ

EMBANKMENT MATTING DETAIL

STD. NO.	REV.
30.20	1