



TYPICAL PAVEMENT SECTION

KEY

- (R) 2'-6" STANDARD CURB AND GUTTER (SHOWN) OR 2'-0" VALLEY GUTTER
- (S) 4" CONCRETE SIDEWALK

NOTES:

1. SIDEWALK IS 5' MIN. WHEN LESS THAN 8 DUA. SIDEWALK IS 6' MIN. WHEN 8 DUA OR GREATER BUT LESS THAN 12 DUA. SIDEWALK IS 8' MIN. WHEN 12 DUA OR GREATER.
2. AN ALTERNATIVE PAVEMENT DESIGN MAY BE REQUIRED BY CDOT/NCDOT BASED ON SPECIFIC TRAFFIC PARAMETERS.
3. AMENITY ZONE (HARDSCAPE) ALLOWED IN LIEU OF PLANTING STRIP WITH PRIOR APPROVAL FROM ENGINEERING, CDOT, AND PLANNING.
4. FOR EXPLANATION OF RIGHT-OF-WAY WIDTHS REFER TO CITY OF CHARLOTTE SUBDIVISION ORDINANCE SECTION 20-22(d).
5. ZONING SETBACKS MEASURED FROM TOTAL R/W.

NOT TO SCALE



CITY OF CHARLOTTE  
LAND DEVELOPMENT STANDARDS  
INCLUDES CHARLOTTE ETJ

LOCAL COLLECTOR STREET  
TYPICAL SECTION

STD. NO.	REV.
U-07	13