



**NO. DESCRIPTION:**

1. 1 11/32" RADIUS.
2. 3/4" RADIUS.
3. 4 1/4" RADIUS.

**NOTES:**

- A. METER BOX SHALL ACCOMMODATE COMPANION PLASTIC METER BOX LID - SEE STANDARD DETAIL.
- B. MINOR DIMENSION VARIATIONS ARE PERMITTED, BASED ON MANUFACTURER'S PRODUCT LINES, PROVIDED THE CLTW STANDARD PLASTIC LID FITS PROPERLY.
- C. CONCRETE SHALL BE MINIMUM  $f_c = 4,000$  PSI COMPRESSIVE STRENGTH.
- D. DESIGN SHALL CONFORM TO ASTM C858-SPECIFICATIONS FOR "UNDERGROUND PRECAST CONCRETE UTILITY".
- E. STEEL REINFORCING DESIGN SHALL CONFORM TO ASTM C857.
- F. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A185 AND A82.
- G. WHEN METER HAS TO BE IN SIDEWALK, USE THIS DETAIL ONLY (CONCRETE BOX).

**MANUFACTURERS:**

SOUTHERN METER #C.H. 2 METER BOX BODY

BOX BODY WEIGHT - 191 LB